




PAR 64 Halogen lamps










Light, bright, cool

A live performance without spotlights? A rock band without a stage show? A discotheque without dazzling light effects? In the entertainment sector, success is largely dependent on a spectacular light show. Therefore, organizers have been relying on PAR lamps for years. Whether used on small or large stages: Our PAR 64 lamps will always be shining stars in show business.

osram.com/entertainment



PAR 64 lamp types

Order reference	64737/4	64738/4	64739/4
ANSI	EXC	EXD	EXE
LIF	CP/60	CP/61	CP/62
Application	Very Narrow Spot	Narrow Spot	Medium Flood
Intended use	 	 	 
Nominal power (W)	1000	1000	1000
On-mode power P _{on} (W)	1035	1035	1035
Rated lamp voltage U (V)	240	240	240
Average service life (h)	300	300	300
Peak luminous intensity (cd)	307,500	255,400	116,000
Colour temperature CTT (K)	3090	3090	3090
Beam angle (horizontal/vertical)	11°/10°	12°/10°	25°/12°
Energy efficiency class (A-G)*			
Base	GX16d	GX16d	GX16d
Bulb diameter d (mm)	204	204	204
LCL a (mm)	102	102	102
Lamp length l (mm)	152.4	152.4	152.4
Product number	4062172359214	4062172359238	4062172359252

*) The energy label and the product information sheet can be obtained from the following website: www.osram.com.



PAR 64 lamps are tried and tested when it comes to producing atmosphere at events of any kind.

Applications

- Events
- Performances
- Stage productions

Features & Benefits

- The parabolic glass reflector and the front lens are fused together
- Easy lamp replacement
- High luminous intensity
- Flexible operating position
- Available in different beam angles to ensure high flexibility

ams OSRAM Group
ams-osram.com

OSRAM GmbH
Marcel-Breuer-Strasse 4
80807 Munich, Germany
Phone +49 89-6213-0
Fax +49 89-6213-2020
www.osram.com