











Discharge - Single Ended Hot Restrike CSR 1800/SE/HR

77390

# **Product information**

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

#### **Application areas**



Film and Broadcast









## **Product data**

G38
Tubular
Clear
42
200
107
285
730
U - Universal
General Electric (GE)

## Performance data

Colour Code	960
Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	6000
Nominal lumens [lm]	165000
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.333
Nominal chromaticity coordinate Y	0.333
Weighted energy consumption [kWh/1000h]	1980

### **Electrical data**

Nominal power [W]	1800
Nominal lamp voltage [V]	150
Lamp Current [A]	12
Dimming Capability	No
Ballast Required	Yes



# Discharge - Single Ended Hot Restrike CSR 1800/SE/HR

77390

#### Logistic data

DUN Code	10043168773901
EAN Code	0043168773904
Pack Quantity	6
Inner pack type	BOX
Layer quantity	36 EUR, 66 UK
Layer quantity EUR	36
Layer quantity UK	66
Pallet quantity EUR (PC)	108
Pallet quantity UK (PC)	132
Outer case size	385 x 280 x 346 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination