











Discharge - Single Ended Hot Restrike CSR18000/SE/HR

22496

# **Product information**

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

#### **Application areas**



Film and Broadcast









## **Product data**

G51
Tubular
Clear
103
470
260
45
1400
2450
U - Universal
General Electric (GE)

## Performance data

Colour Code	960
Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	6000
Nominal lumens [lm]	1650000
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.323
Nominal chromaticity coordinate Y	0.325
Weighted energy consumption [kWh/1000h]	19800

## **Electrical data**

Nominal power [W]	18000
Nominal lamp voltage [V]	225
Lamp Current [A]	80
Dimming Capability	No
Ballast Required	No



# Discharge - Single Ended Hot Restrike CSR18000/SE/HR

22496

#### Logistic data

DUN Code	10043168224960
EAN Code	0043168224963
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	4 EUR, 4 UK
Layer quantity EUR	4
Layer quantity UK	4
Pallet quantity EUR (PC)	16
Pallet quantity UK (PC)	16
Outer case size	280 x 270 x 705 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination