











Discharge - Double Ended Hot Restrike CSR575/S/DE/70

70979

# **Product information**

Double ended compact source rare earth metal halide hot restrike lamps from GE can be used in a variety of applications requiring high luminance, reliability and excellent colour characteristics. Industry Standard outline with hot restrike capability- Dimmable with stable colour- High efficiency with excellent lumen maintenance.

#### **Application areas**



**Event and Tour** 



Film and Broadcast







70979

## **Product data**

Cap/Base	SFc10-4
Bulb Finish	Clear
Bulb Diameter [mm]	21
Maximum Overall Length [mm]	138
Arc Gap	7
Net weight per piece [g]	34
Gross weight per piece [g]	130
Operating position	U - Universal
Brand	General Electric (GE)

## Performance data

770
75
7000
40000
А
0.307
0.309
632.5

## **Electrical data**

Nominal power [W]	575
Nominal lamp voltage [V]	95
Lamp Current [A]	6.1
Dimming Capability	No
Ballast Required	Yes



# Discharge - Double Ended Hot Restrike CSR575/S/DE/70

70979

### Logistic data

DUN Code	10043168709795
EAN Code	0043168709798
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	260 EUR, 330 UK
Layer quantity EUR	260
Layer quantity UK	330
Pallet quantity EUR (PC)	1040
Pallet quantity UK (PC)	1320
Outer case size	208 x 166 x 280 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination