

HMI 575 W/DXS

HMI | Metal halide lamps, double-ended



Technical data


Electrical data

Nominal wattage	575 W
Lamp wattage	575 W
Nominal voltage	95.0 V
Lamp voltage	95 V
Nominal current	7 A
Lamp current	7.00000 A

Photometrical data

Luminous flux	49000 lm
Color temperature	6000 K
Color rendering index Ra	90

Dimensions & weight



Diameter	21.0 mm
Length	135.0 mm
Mounting length	115.0 mm
Length with base excl. base pins/connection	115.00 mm

Lifespan

Lifespan	1000 h
----------	--------

Additional product data

Base (standard designation)	SFc10-4
-----------------------------	---------

Capabilities

Burning position	Any
------------------	-----

Product datasheet

Certificates & standards

EEI – Energy Label	B
--------------------	---

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4008321285102	OSRHMI575DXS	-	4836416	-

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321285102	HMI 575 W/DXS	Shipping carton box 1	245 mm x 59 mm x 100 mm	1.45 dm ³	148.00 g
4008321285119	HMI 575 W/DXS	Shipping carton box 10	259 mm x 315 mm x 214 mm	17.46 dm ³	1454.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
