



KTDL34GL

34w LED Global Track Downlight, 40000hrs



Product Overview

The Kosnic LED Tracklight is suitable for use with the Global 3 Circuit Track System. With a 350 degree rotation and 180 degree tilt, the Kosnic LED Tracklight is able to deliver a lot of light right where you need it. The LED Tracklight is particularly suitable for retail display, showrooms, galleries, and museums.

Features

Simple and elegant appearance.

Uniform soft light for perfect presentation without dark areas.

Easy to install with Global 3 Circuit Track System.

High CRI.

High lumen output.

Long life of 40,000h.

Instant start.

Negligible UV output.

Mercury free.

Specifications


	KTDL34GL-B30 ^[1]	KTDL34GL-B40 ^[1]	KTDL34GL-B50 ^[1]
	KTDL34GL-S30 ^[2]	KTDL34GL-S40 ^[2]	KTDL34GL-S50 ^[2]
Shape / Type	Tracklight	-	Tracklight
Colour Finish	White	-	White
Materials	Diecast Aluminium	-	Diecast Aluminium
Optics Type	Reflector	-	Reflector
Wattage (w)	34	-	34
Total Lumens (lm)	2800 ^[1] 2300 ^[2]	-	3100 ^[1] 2900 ^[2]
Input Current (mA)	155	-	155
Input Voltage	220-240Vac	-	220-240Vac
CCT Temperature (k)	3000	-	5000
CCT Name	Warm White	-	Day Light
Rated Life (hrs)	40000	-	40000
Nominal Lifetime (hrs)	40000	-	40000
Switch Cycles	50000	-	50000
Peak Candelas (cd)	25500 ^[1] 5030 ^[2]	-	27600 ^[1] 5680 ^[2]
Beam Angle (°)	15 ^[1] 40 ^[2]	-	15 ^[1] 40 ^[2]
CRI	82	-	82
Dimmable	No	-	No
Suitable for Accent Lighting	Yes	-	Yes
Power Factor	0.95	-	0.95
IP Rating	IP20	-	IP20

Class Protection	Class I	-	Class I
Connection	Global 3 Circuit Track	-	Global 3 Circuit Track
Start Time (s)	0.1	-	0.1
Warm-up Time (s)	Instant full light	-	Instant full light
Length (mm)	207	-	207
Width (mm)	97	-	97
Depth (mm)	152.5	-	152.5
Mercury (mg)	0	-	0
Rated Power (W)	34.00	-	34.00
Rated Luminous Flux (lm)	2800 ^[1] 2300 ^[2]	-	3100 ^[1] 2900 ^[2]
LMF at Lifetime	0.75	-	0.75
SDCM of CCT	<6	-	<6
Ambient Temperature (°C)	-20 to 50	-	-20 to 50


Packaging

	KTDL34GL-B30 ^[1]	KTDL34GL-B40 ^[1]	KTDL34GL-B50 ^[1]
	KTDL34GL-S30 ^[2]	KTDL34GL-S40 ^[2]	KTDL34GL-S50 ^[2]
Outer Box Length (mm)	525	-	525
Outer Box Width (mm)	370	-	370
Outer Box Height (mm)	320	-	320
Volume	0.06216	-	0.06216
Box Quantity	8	-	8
Outer Box Weight (kg)	11.5	-	11.5


KTDL34GL-B30
KTDL34GL-B40
KTDL34GL-B50
KTDL34GL-S30
KTDL34GL-S40
KTDL34GL-S50




KTDL34GL-B30
KTDL34GL-S30



KTDL34GL-B50
KTDL34GL-S50



KTDL34GL-B30
KTDL34GL-B40
KTDL34GL-B50
KTDL34GL-S30
KTDL34GL-S40
KTDL34GL-S50



Datasheet generated from <http://www.electrika.com> last updated Tuesday, May 22, 2018 10:53:48 AM