# Magical Full-house effect light

The RUSH Wizard is the Martin Wizard Extreme re-energized: lighter, brighter, more compact and even more energy efficient. This music triggered and DMX-Controllable "full-house" effect light, features extraordinary bright and magical effects. It features a color wheel with seven colors and a gobo wheel with 15 gobos, as well as a shutter for strobe and pulse effects. The Wizard delivers more than 80 agile light beams, each beam chasing the other while continuously changing color and gobo pattern.

- 130 W short-arc discharge lamp with reflector
- 15 gobos plus open
- More than 80 magical light beams
- 7 colors + 2 open
- Shutter: Strobe effect, pulse effects, instant open and blackout
- Adjustable focus
- DMX or stand-alone mode
- Flexible mounting bracket for floor stand, wall or overhead mounting

# **Technical specs**

\_. . .

Physical
Length: 447 mm (17.6 in.
Width: 500 mm (19.7 in.)
Height: 195 mm (7.7 in.)
Weight: 9.3 kg (20.5 lbs.) including bracket
Lamp
Type: 130 W short-arc discharge with reflector
Color temperature: 8800 K
Average lifetime: 6000 hours*
*Manufacturer's figure
Dynamic Effects
Motorized rotating parabolic mirror dish
Color / animation wheel: 7 colors plus 2 x open, twinkle animation effect
Gobo wheel: 15 gobos + open, wheel scrolling and continuous rotation, shake effect
Shutter: 0 - 100% continuous dimming, variable & random strobe & pulse effects, instant open & blackout
Motorized mirror drum: 180° pan (swivel) and 360° tilt (continuous rotation)
Pre-programmed effects: Full range of macro effects
Control and Programming
Control options: DMX, stand-alone, master/slave
DMX channels: 10
Stand-alone trigger options: Music trig, auto trig
Music trig also settable via DMX
Setting and addressing: Control panel with backlit LCD display
Protocol: USITT DMX512/1990
Firmware update: Serial upload via DMX link
Optics
Manual focus: 2 m (6.6 ft.) - 20 m (65.6 ft.)
Construction
Housing: High-impact flame-retardant thermoplastic
Color(s): Black
Protection rating: IP20
Installation
Mounting points: Adjustable bracket
Orientation: Any
Location: Indoor use only, must be fastened to surface or structure
Minimum distance to illuminated surfaces: 0.5 m (1.6 ft.)
Minimum distance to combustible materials: 0.3 m (1.0 ft.)
Minimum clearance around fan and air vents: 0.3 m (1.0 ft.)

#### Connections

	'thru: Neutrik PowerCon
DMX data in/	'out: 5-pin locking XLR
Electrical	
AC power: 1	00-240 V nominal, 50/60 Hz
Typical total p	power consumption: 200 W
Power consu	imption figures are typical, not maximum. Allow for +/-10% variation.
Thermal	
	ced air (temperature-regulated, low noise)
Maximum an	nbient temperature (Ta max.): 40° C (104° F)
Minimum am	bient temperature: 0° C (32° F)
Total heat dis	sipation (calculated, +/- 10%): 685 BTU/hr.
Approvals	
<u></u>	N 60598-2-17 (EN 60598-1), EN 62471, EN 62493
EU safety: EN	
EU safety: EN	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547
EU safety: EN EU EMC: EN US safety: UI	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547
EU safety: EN EU EMC: EN US safety: UI US EMC: FC	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547 L 1573
EU safety: EN EU EMC: EN US safety: UI US EMC: FC Canadian saf	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547 L 1573 C Part 15 Class A
EU safety: EN EU EMC: EN US safety: UI US EMC: FC Canadian sat Canadian EM	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547 L 1573 C Part 15 Class A fety: CSA C22.2 No. 166
EU safety: EN EU EMC: EN US safety: UI US EMC: FC Canadian sat Canadian EM	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547 L 1573 C Part 15 Class A feiy: CSA C22.2 No. 166 IC: ICES-003 Class A
EU safety: EN EU EMC: EN US safety: UI US EMC: FC Canadian sat Canadian EM	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547 L 1573 C Part 15 Class A fety: CSA C22.2 No. 166 IC: ICES-003 Class A C-TICK N4241
EU safety: EN EU EMC: EN US safety: UI US EMC: FC Canadian saf Canadian EM Australia/NZ:	55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547 L 1573 C Part 15 Class A fety: CSA C22.2 No. 166 IC: ICES-003 Class A C-TICK N4241 ms

ounting bracke Power cable, 1.5 m (4.9 ft.), without mains plug

## Accessories

G-clamp: P/N 91602003 Half-coupler clamp: P/N 91602005 DMX termination plug, 3-pin male XLR: P/N 91613017 5-pin male XLR to 3-pin female XLR adaptor: P/N 11820005 Safety cable, safe working load 50 kg (110.2 lbs.): P/N 91604003

#### **Related Items**

RUSH Software Uploader 1<sup>™</sup> : P/N 91611399

#### **Ordering Information**

USH Wizard™ in cardboard box, EU model P/N 90480070 RUSH Wizard™ in cardboard box, US model P/N 90480075

Specifications are subject to change without notice. For the latest product specifications, see www.martin.com



### Martin Professional Olof Palmes Allé 18 • 8200 Aarhus N • Denmark • Phone: +45 87 40 00 00 • Fax: +45 87 40 00 10 • www.martin.com

#### About Martin Professional

As a world leader in the creation of dynamic lighting solutions for the entertainment, architectural, and commercial sectors, Martin lighting and video systems are renowned the world over. Martin also offers a range of advanced lighting controllers and media servers, as well as a complete line of smoke machines as a complement to intelligent lighting. Martin operates the industry's most complete and capable distributor network with local partners in nearly 100 countries. Founded in 1987 and based in Aarhus, Denmark, Martin is the lighting division of global infotainment and audio company HARMAN International Industries. HARMAN (www.HARMAN.com) designs, manufactures and markets a wide range of audio and infotainment solutions for the automotive, consumer and professional markets – supported by 15 leading brands, including AKG®, Harman Kardon®, Infinity®, JBL®, Lexicon® and Mark Levinson®. The Company is admired by audiophiles across multiple generations and supports leading professional entertainers and the venues where they perform. More than 25 million automobiles on the road today are equipped with HARMAN audio and infotainment systems. HARMAN's highly competent workforce is employed across the Americas, Europe and Asia

For more information please visit

f 🛅 🎔 in 🖸 🔶

C2014 Martin Professional Images contained in this brochure have been converted to CMYK and are not necessarily representative of actual colors. Specifications are subject to change without notice