JIUNGSRAM[™]

Innovation is our heritage EST.1896





Single Ended Halogen T29 FWT 230-240V 88454

Product information


Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs - Chromised seal protection up to 500° C.

Application areas



Film and Broadcast 🗊 Theatre







Product data

Light Center Length [mm]	67
Product Code	88454
Bulb Shape	Tubular
Bulb Diameter [mm]	35
Maximum Overall Length [mm]	124
Net weight per piece [g]	45
Gross weight per piece [g]	150
Brand	GE Lighting
Cap/Base	GX9.5

Performance data

Weighted energy consumption [kWh/1000h]	1193.38
Energy efficiency class (EEC)	C
Rated Life [h]	400
Nominal correlated colour temperature (CCT) [K]]	3050
Nominal lumens [lm]	29000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	C-13D
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	1200
Nominal lamp voltage [V]	240

Logistic data

DUN Code	10043168884546
EAN Code	0043168884549
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR, 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	190 x 350 x 126 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.