

26782

Screen/Monitor Stand



Product variant

26782-000-56 - structured black

Data

Base dimensions	420 x 420 mm
Height	from 1,100 to 1,650 mm
Height adjustment	spring-loaded clamping knob
Leg construction	cast-iron base
Material	steel
Mounting device	VESA MIS-D 100 (100x100) - ground plate, VESA MIS-E 200 (200x100) - ground plate, VESA MIS-E 200 (100x200) - with adapter bars, VESA MIS-F 200 (200x200) - with adapter bars, VESA MIS-F - with universal bracket: 250 to 600 mm horizontal 150 to 400 mm vertical
Rod combination	2-piece folding design
Special features	internal cable routing possible; installation material (M4/M6/M8) and assembly tools included
Suitable for	flat screens from 24" to 46"
Type	structured black
Weight	15.2



A representative screen/monitor stand with a beautifully designed heavy cast iron base. The assembly accessories provided with the product allow one to set up according to the VESA Standard for 24" to 46" flat screens. The large tubing saves space by providing a place to organize and store the cables. The height can be adjusted in steps using an ergonomic height adjustment screw.

26782

Bildschirmstativ



Produktvariante

26782-000-56 - schwarz struktur

Daten

Aufstellmaß	420 x 420 mm
Ausführung	schwarz struktur
Besonderheit	Kabelführung innen möglich; inklusive Montagematerial (M4/M6/M8) und Montagewerkzeug
Bildschirmhalterung	VESA MIS-D 100 (100x100) - Basisplatte, VESA MIS-E 200 (200x100) - Basisplatte, VESA MIS-E 200 (100x200) - mit Adapterleisten, VESA MIS-F 200 (200x200) - mit Adapterleisten, VESA MIS-F - mit Universalhalterung: 250 bis 600 mm horizontal 150 bis 400 mm vertikal
Fußkonstruktion	Guss-Sockel
Gewicht	15,2
Höhe	von 1.100 bis 1.650 mm
Höhenverstellung	Rast- und Klemmschraube
Material	Stahl
passend für	Flachbildschirme von 24" bis 46"
Rohrkombination	1-fach ausziehbar



Repräsentatives Bildschirmstativ mit formschönem, schwerem Gusssockel. Das mitgelieferte Montagezubehör ermöglicht die Befestigung nach VESA-Standard für Flachbildschirme von 24" bis 46". In der groß dimensionierten Rohrkombination werden die Kabel platzsparend und übersichtlich aufgenommen. Die Höhenverstellung erfolgt stufenweise mittels einer ergonomischen Rast-Klemmschraube.