











Discharge - Single Ended Hot Restrike csr200/se/hr/uv-c

48462

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

Application areas



Film and Broadcast









Product data

Cap/Base	GZY9.5
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	19.1
Maximum Overall Length [mm]	80
Light Center Length [mm]	38.8
Net weight per piece [g]	19
Gross weight per piece [g]	200
Operating position	U - Universal
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	6000
Nominal lumens [lm]	17500
Energy efficiency class (EEC)	А
Nominal chromaticity coordinate X	0.333
Nominal chromaticity coordinate Y	0.3237
Weighted energy consumption [kWh/1000h]	220

Electrical data

Nominal power [W]	200
Nominal lamp voltage [V]	70
Lamp Current [A]	2.9
Dimming Capability	No
Ballast Required	Yes



Discharge - Single Ended Hot Restrike CSR200/SE/HR/UV-C

48462

Logistic data

DUN Code	00043168484626
EAN Code	0043168484626
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	480 EUR, 600 UK
Layer quantity EUR	480
Layer quantity UK	600
Pallet quantity EUR (PC)	5280
Pallet quantity UK (PC)	5400
Outer case size	195 x 84 x 100 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination