



AEOS 2 PRO



MOVE. SHOOT. CREATE



HIGH SPEED
RGBWW FLASH



16.7M COLOURS
(RGBWW)



2500 DIGITAL
FILTERS



TOUCHSCREEN
DISPLAY



NATIVE IOS &
ANDROID APP



[ROTOLIGHT.COM/AEOS2PRO](https://rotolight.com/aeos2pro)



AEOS 2 PRO

RL-AEOS2-PRO

DOME | YOKE | PSU



IMAGEMAKER KIT

RL-AEOS2-PRO-IK

DOME | BATTERY | BAG | YOKE



TRAVELLER KIT

RL-AEOS2PRO-TK

2X LIGHTS | DOMES | BATTERIES | BAG | YOKES | STANDS

AEOS 2 PRO REVIEWS

"A PORTABLE, PROFESSIONAL POWERHOUSE, AEOS 2 PRO IS BY FAR THE BEST LED LIGHT PANEL WE'VE EVER USED"

DIGITAL CAMERA WORLD



"TRULY GREAT, AEOS 2 PRO IS WELL WORTH THE INVESTMENT"

PETAPIXEL



"THE ABILITY TO BE USED AS BOTH AN HSS FLASH OR A CONSTANT LIGHT MAKES THE AEOS 2 PRO A VERY COMPELLING OPTION"

NEWSSHOOTER



TECHNICAL SPECIFICATIONS

With the AEOS 2 PRO, the world is your studio. Combining the shoot what you see benefits of powerful continuous light with a High Speed RGBWW strobe, AEOS 2 PRO offers unmatched versatility for photographers and filmmakers. Uniquely lightweight with an ultra-thin design, it's never been easier to achieve beautiful soft light on the move.

TECH SPECS	
Peak Output (Lux) @ 3ft	11,700 (continuous) 17,500 (flash)
Lux at 3ft F-stop at ISO 100/200/400	11,700 F13/ F18/ F22
Lux at 6ft F-stop at ISO 100/200/400	2950 F6.3/ F9/ F11
Lux at 9ft F-stop at ISO 100/200/400	1430 F3.5/ F4.5/ F6.3
TLCI	99
CRI	95
Power Consumption	120W
Battery Type	V-lock 14.4V, 100W minimum
Mounting	1/4" - 20 tripod or optional Yoke
Dimensions	W: 295mm (11.5") x D 25mm (1")
Wireless Control	WIFI & Bluetooth via IOS & Android app
Beam Angle	50 degrees
Max Shutter Speed Sync	1/8000
Min Flash Duration	1/2500

	AEOS 2 PRO	Rotolight AEOS 2	Litepanel Astra 6X Bi	Litepanel Gemini 1x1 soft	Luxli Timpani 1x1 RGBWW
Touchscreen Interface	✓	✓	✗	✗	✗
Electronic Diffusion	✓	✓	✗	✗	✗
High Speed Sync Flash	✓	✓	✗	✗	✗
Digital Filters	2500	2500	✗	600	150
Colour Accuracy TLCI	99	99	95	97	95
Weight	1.4kg	1.4kg	3.2kg	5.31kg	3.15kg
Power Consumption	120W	120W	105W	200W	120W
Kelvin Range	3000-10000 Kelvin	3000-10000 Kelvin	3200-5600 Kelvin	2700-10000 Kelvin	2800-10000 Kelvin
FDIM	✓	✗	✗	✗	✗
Master of Light Presets	100+	✗	✗	✗	✗
Wireless Trigger Compatibility	Godox, Profoto, Elicrom, Pixapro, Neweer	Elinchrom Skyport	✗	✗	✗
Peak Brightness (1m) (lux)	9477	7800	2651	5544	3430

*Lux measured at 4600k using Sekonic c7000 using firmware 3.01, readings may vary depending on light meter used and testing environment.

All third-party photometrics taken from latest product information sheets and bhphoto.com, accessed in November 2022. Rotolight, AEOS, Aperture, Litepanels, Profoto, Godox & Luxli are registered trademarks and the exclusive property of their respective owners. No association is intended or implied. Pricing based on full retail prices in USD at Bhphoto.com as of November 2022.