

info@lemark.co.uk



(UK) 01480 494540 (Int.) +44 1480 494540



www.lemark.co.uk

Le Mark Group Ltd., 1 Houghton Hill Ind., Sawtry Way, Houghton, Cambridgeshire, PE28 2DH England

Registered in England 1761971 VAT No. GB 395772693







@lemarkgroup

MAGTAPE XTRA CHROMA MATT

Product Description

65% (Polyester) + 35% (Cotton) Woven Cloth with Warp & Weft Natural rubber base adhesive

Part number: MATTCHROMA

Technical Specification

Mesh	80
Total Thickness (Micron)	300
Peel adhesion (gf/25mm/180°)	1,250
Tensile strength (kgf/25mm)	14.5
Elongation (%)	9.5
Ball tack (Ball No.)	22
Holding power (Min') ※1kg loading on SUS plate, 25mm×25mm at	45
40 Celsius	
Un-winding force (gf/25mm)	1000
Heat resistance (°C/min)	85/180
Weather resistance (Hrs)	8
Average Weight (g) - 50mm	860
Delamination	No

Above test were performed on the condition of 23±2 $^{\circ}$ C and humidity of 65±5% (JIS Z 0237, 1254) All above data can be changed according to testing circumstances. This is to certify that our products are identified with the specification as indicated above, and declare that JIS Z 0237, 1254 is fundamentally the same as American Spec sat-do 5486.

Storage

This item should be stored at room temperature, away from direct sunlight and damp.

TAPES LABELS FLOORS CREW WEAR

Disclaimer

PLEASE NOTE: Stated performance figures and specification are based on average values and should not be regarded as maximum or minimum values. Measurements are approximate. Due to the nature of this product, performance may deteriorate over time. Due to varying application environments, the suggested uses should be considered as a general guide only. We recommend all users assess the suitability of our products for their individual application. Although we make all reasonable efforts to ensure the accuracy of information shown at time of print, we recommend contacting us for up to date product information prior to ordering.

Version Number: 1

Last revision date: 07/10/24

TAPES LABELS FLOORS CREW WEAR