



— PRODUCT DATA SHEET

P3R



P3R

PRODUCT DESCRIPTION

Not to be underestimated: The P3R key flashlight is equipped with the tried-and-tested Advanced Focus System for easy focusing to create an ideal light pattern for any range. It operates with both rechargeable and disposable batteries. Besides, all aluminium components are made of 75 % recycled material.



- Rechargeable key flashlight with focus function (Advanced Focus System) and three brightness levels
- Dual Power Source: Operates with rechargeable and disposable batteries, charging via USB-C on battery (charging cable not included)
- Intuitive operation via End Cap Switch
- Sustainable: Use of 75 % recycled aluminium⁹ and 7-year warranty*
- Keyring to safely attach the flashlight to your keys or backpack

TECHNICAL DATA	
Weight incl. batteries [g]	41
Material	Aluminum alloy
Length [mm]	94
Length (focused) [mm]	98
Tube diameter [mm]	15
Head diameter [mm]	20
POWER SUPPLY	
Battery quantity	1
Rechargeable	Yes
Battery type	Lithium-ion
Total battery voltage [V]	3.7
Total battery capacity [mAh]	300
Total battery energy [Wh]	1.11 Wh
Battery replaceable	Yes
Charging time [min]	90
Useable batteries	Micro (AAA) 1.5V, AAA NiMH 1.2V
FURTHER SPECIFICATIONS	
IP class	IP54
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS			
Cool White Main: Power, Mid power, Low power			
LIGHT SOURCE		MAIN	
Amount LEDs		1	
Color		Cool White	
Color temperature [K]		6000 to 7500	
Color rendering index (CRI)		70	
LIGHT VALUES - Cool White Main			
	Power	Mid power	Low power
Light output [lm]	200	80	20
Beam distance [m]	130	80	40
Run time [h]	1.5	2.5	8
SWITCH			
End-cap Switch			
TECHNOLOGIES			
Advanced Focus System, Dual Power Source, Rapid Focus			

P3R

PACKAGING AND LOGISTICS



For illustration purposes only

PACKAGING INFORMATION	
Type of packaging	Box
Scope of delivery	Key ring, 10440 Li-ion USB-C direct charging battery
Item No.	503107
Color	Black
MSRP price (€)	39,90

SINGLE PACKAGE	
Dimensions W x H x D [cm]	14.5 x 8.5 x 4.2
Gross weight [g]	94.5
GTIN-13	4058205037259

EXPORT CARTON	
Unit	24
Dimensions W x H x D [cm]	37.5 x 17 x 31
Gross weight [g]	2930
GTIN-13	4058205037235

P3R

PRODUCT SERIES

Powerful flashlights for those who push boundaries—the discerning enthusiasts, the industrious workers, the bold adventurers and the forward-thinkers. Lights that bridge the gap between the epic and the technical. In your hand, they do more than shine—they guide your path, reveal the unknown and empower you to explore, discover and redefine what is possible. Pioneering Brilliance. The P-Series: Redefined.

P3R

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

*) 7 year warranty only if registered, otherwise 2 years.
Warranty conditions viewable at <https://ledlenser.com/en/infos-service/warranty/>

1) Measured values according to ANSI/PLATO FL 1 in the respective setting named. If no setting is specifically named, the luminous flux (lumens/lm) and range (meters/m) values refer to the brightest setting and the burn time

(hours/h) values refer to the lowest setting. A boost function (if available) can be used several times, but is only available for a short time at a time. In case the lamp is equipped with colored LED(s), the measured values are given with white light or the white LED. If the lamp has different energy modes, the "energy saving mode" is the basis for the measurement.

2) Calculated value of the capacity in watt-hours (Wh). This applies to the battery(ies) contained in the delivery condition of the respective item or, in the case of lamps with rechargeable battery, to the battery(ies) contained herein in a fully charged condition.

9) All aluminium components are made of at least 75 % recycled aluminium and may thus vary in surface structure and color.