



— PRODUCT DATA SHEET

P7



P7

PRODUCT DESCRIPTION

The Ledlenser P7 flashlight is the stuff of legends: It fits in the palm of your hand, comes with a long-range focus and has an even higher light output than its predecessor. The high-quality housing and all other aluminium components are made of 75 % recycled material, a pledge to the sustainable use of resources at Ledlenser. Ideal for illuminating large rooms and to keep at hand in case of power outages.



- Brilliant light quality and focus function (Advanced Focus System) with impressive beam range
- Intuitive operation via End Cap Switch
- Operates with four AAA alkaline batteries
- Sustainable: Use of 75 % recycled aluminium⁹
- Backed by a 7-year warranty*

| TECHNICAL DATA | |
|--------------------------------|----------------|
| Weight incl. batteries [g] | 175 |
| Material | Aluminum alloy |
| Length [mm] | 131 |
| Length (focused) [mm] | 140 |
| Tube diameter [mm] | 30 |
| Head diameter [mm] | 37 |
| POWER SUPPLY | |
| Battery quantity | 4 |
| Rechargeable | No |
| Battery type | Alkaline |
| Total battery voltage [V] | 1.5 |
| Total battery capacity [mAh] | 0 |
| Total battery energy [Wh] | 0 Wh |
| Useable batteries | AAA NiMH 1.2V |
| FURTHER SPECIFICATIONS | |
| IP class | IP54 |
| Drop test (drop height) [m] | 1 |
| Working temperature range [°C] | -20 to +40 |

| LIGHT FUNCTIONS | | | |
|--|-------|--------------|-----------|
| Cool White Main: Power, Mid power, Low power | | | |
| LIGHT SOURCE | | MAIN | |
| Amount LEDs | | 1 | |
| Color | | Cool White | |
| Color temperature [K] | | 6000 to 7500 | |
| Color rendering index (CRI) | | 70 | |
| LIGHT VALUES - Cool White Main | | | |
| | Power | Mid power | Low power |
| Light output [lm] | 650 | 300 | 40 |
| Beam distance [m] | 400 | 250 | 85 |
| Run time [h] | 1 | 3 | 30 |
| SWITCH | | | |
| End-cap Switch | | | |
| TECHNOLOGIES | | | |
| Advanced Focus System, Rapid Focus | | | |

P7

PACKAGING AND LOGISTICS



For illustration purposes only

| PACKAGING INFORMATION | |
|---------------------------|--|
| Type of packaging | Box |
| Scope of delivery | 1 set of batteries - AAA, Adjustable Lanyard |
| Item No. | 503102 |
| Color | Black |
| MSRP price (€) | 74,90 |
| SINGLE PACKAGE | |
| Dimensions W x H x D [cm] | 7.2 x 21 x 4.2 |
| Gross weight [g] | 250 |
| GTIN-13 | 4058205037105 |
| EXPORT CARTON | |
| Unit | 24 |
| Dimensions W x H x D [cm] | 44.5 x 17.5 x 31 |
| Gross weight [g] | 6700 |
| GTIN-13 | 4058205037082 |

P7

PRODUCT SERIES

Powerful flashlights for those who push boundaries—the discerning enthusiasts, the industrious workers, the bold adventurers and the forward-thinkers. Lights that bridge the gap between the epic and the technical. In your hand, they do more than shine—they guide your path, reveal the unknown and empower you to explore, discover and redefine what is possible. Pioneering Brilliance. The P-Series: Redefined.

P7

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

*) 7 year warranty only if registered, otherwise 2 years.
Warranty conditions viewable at <https://ledlenser.com/en/infos-service/warranty/>

1) Measured values according to ANSI/PLATO FL 1 in the respective setting named. If no setting is specifically named, the luminous flux (lumens/lm) and range (meters/m) values refer to the brightest setting and the burn time (hours/h) values refer to the lowest setting. A boost function (if available) can be used several times, but is only available for a short time at a time. In case the lamp is equipped with colored LED(s), the measured values are given with white light or the white LED. If the lamp has different energy modes, the "energy saving mode" is the basis for the measurement.

9) All aluminium components are made of at least 75 % recycled aluminium and may thus vary in surface structure and color.