



## ART-BLINDONE

Blinder led 300W RGB+WW modulaire Art by Flash

### Power Source (AC)

Supply voltage	100-240V
Power consumption	350W
Power consumption (peak)	500W
Power frequency	50-60Hz

### Light source

Type	LED (RGBWA)
Quantity	1
Power (W)	550W
Color temperature	2000
Color temperature	10000
Color Rendering Index (CRI / Ra)	96

### Color Mixing System

RGBWA	16 bit
-------	--------

### Dimming

Dimming	16 bit
---------	--------

### ZOOM

ZOOM	Fixed
------	-------

### Beam angle

Beam angle	Stały (50°)
------------	-------------

### Strobe - frequency

Frequency	1-20Hz
Pulsating	Yes
Random	Yes

### DMX control

Number of modes	15
Number of channels	1-23

### Modes of operation

DMX512	Yes
RDM	Yes

**User Interface**

Capacitive (touch) buttons	Yes
Color display	Yes

**Connectors**

AC IN	TrueCon IP65
AC OUT	TrueCon IP65
DMX IN	5-pin DMX IP65
DMX OUT	5-pin DMX IP65

**Physical parameters**

IP protection level	IP65
Housing type	Aluminium
Fixing	Mounting hole
Housing Color	Black
Cooling	Active
Length [cm]	19.5
Width [cm]	14.5
Height [cm]	14.5
Weight [kg]	2.4