



Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Fall arrest lanyards




ABSORBICA®-I 150


ABSORBICA-I 150 is a single lanyard with a compact energy absorber, designed for progression on a horizontal lifeline (rope or cable) or on an elevated platform, without passing intermediate anchors. It works with users who weigh between 60 and 140 kg. It has several connection options on the harness and can be used with different types of connectors.



The energy absorber's very compact design doesn't hinder the user during progression.



In the event of a fall, the progressive tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 60 and 140 kg.



To help maximize safety during operations, Petzl offers a simple and quick clearance calculator, determined using user weight and lanyard length. Available at [Petzl.com](https://www.petzl.com).



The pouch's simple opening system gives the user quick access to the energy absorber to perform regular inspections.

Short Description Single lanyard with integrated energy absorber

- Selling Points
- Designed for progression on a horizontal lifeline (rope or cable) or on an elevated platform, without passing intermediate anchors
 - Absorbs energy in the event of a fall:
 - Progressive tearing of the energy absorber webbing limits the impact force on the user
 - Works with users who weigh between 60 and 140 kg (1)
 - Designed for use with a maximum length (including connectors) of:
 - 200 cm under the CE EN 355 standard
 - 183 cm (6 feet) under the ANSI Z359.13
 - Minimal bulk:
 - Energy absorber's very compact design doesn't hinder the user during progression
 - Elasticized arm to avoid hindering progression
 - Durable fabric pouch with a simple opening system protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
 - Two options for installation on the harness, depending on use:
 - Frequent connection/disconnection: with a carabiner held in correct position by the STRING positioning accessory (included with the lanyard)
 - Semi-permanent connection: with a RING OPEN gated ring, whose circular shape allows optimal positioning
 - Two connector options for the end of the lanyard: a locking carabiner or MGO OPEN connector with large gate opening
- (1) Under the CSA Z259.11-17 standard, the user must weigh between 75 and 140 kg.
-

- Specification
- Certification(s):
 - CE EN 355 (meets the requirements of the RFU PPE-R/11.074)
 - ANSI Z359.13, 12 ft. FF
 - CSA Z259.11-17
 - Compliant with the Japanese standard for fall protection
 - GB/T 24538-2009: type II
 - Certifications depend on the connectors that are used. More information in the Instructions for Use.
 - Maximum authorized length with connectors:
 - 200 cm under the CE EN 355, GB/T 24538: type II standards and the Japanese standard for fall protection
 - 183 cm (6 feet) under the ANSI Z359.13 and CSA Z259.11-17 standards
 - Material(s): Polyester, nylon
-

Specifications by reference

Reference(s)	L013AB01
Length without connectors	153 cm
x	200 cm
x	183 cm
Weight	225 g
Made in	RO
Guarantee	3 years
Inner Pack Count	1
Quantity Per Box	10
EAN	3342540846074

Related product(s)	MGO OPEN EASHOOK OPEN Am'D OK Bm'D MICRO SWIVEL RING OPEN SWIVEL OPEN NEWTON EASYFIT International Version VOLT® International Version
--------------------	---