

Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Fall arrest lanyards




ABSORBICA®-I VARIO


ABSORBICA-I VARIO is an adjustable single lanyard with compact energy absorber designed for progression on a horizontal lifeline (rope or cable) or on an elevated platform, without passing intermediate anchors. It works with users who weigh between 60 and 140 kg. It features the VARIO adjustment system, allowing the lanyard length to be adjusted in order to reduce potential fall height.



The VARIO adjustment system can be operated with one hand and allows the user to easily adjust the lanyard length to limit potential fall height.



In the event of a fall, the progressive tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 60 and 140 kg.



To help maximize safety during operations, Petzl offers a simple and quick clearance calculator, determined using user weight and lanyard length. Available at [Petzl.com](https://www.petzl.com).



The pouch's simple opening system gives the user quick access to the energy absorber to perform regular inspections.

Short Description Adjustable single lanyard with integrated energy absorber

Selling Points

- Designed for progression on a horizontal lifeline (rope or cable) or on an elevated platform, without passing intermediate anchors
- VARIO adjustment system allows the lanyard length to be adjusted from 70 to 167 cm (without connector) in order to reduce potential fall height
- Absorbs energy in the event of a fall:
 - Progressive tearing of the energy absorber webbing limits the impact force on the user
 - Works with users who weigh between 60 and 140 kg (1)
- Designed for use with a maximum length (including connectors) of:
 - 200 cm under the CE EN 355 standard
 - 183 cm (6 feet) under the ANSI Z359.13
- Minimal bulk: compact energy absorber facilitates handling
- Durable fabric pouch with a simple opening system protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
- Two options for installation on the harness, depending on use:
 - Frequent connection/disconnection: with a carabiner held in correct position by the STRING positioning accessory (included with the lanyard)
 - Semi-permanent connection: with a RING OPEN gated ring, whose circular shape allows optimal positioning
- Two connector options for the end of the lanyard: a locking carabiner or MGO OPEN connector with large gate opening

(1) Under the CSA Z259.11-17 standard, the user must weigh between 75 and 140 kg.

Specification

- Certification(s):
 - CE EN 355 (meets the requirements of the RFU PPE-R/11.074)
 - ANSI Z359.13, 12 ft. FF
 - CSA Z259.11-17
 - Compliant with the Japanese standard for fall protection
 - GB/T 24538: type II
- Certifications depend on the connectors that are used. More information in the Instructions for Use.
- Maximum authorized length with connectors:
 - 200 cm under the CE EN 355, GB/T 24538: type II standards and the Japanese standard for fall protection
 - 183 cm (6 feet) under the ANSI Z359.13 and CSA Z259.11-17 standards
- Material(s): Polyester, nylon, steel

Specifications by reference

Reference(s)	L016AB00
Length without connectors	70 - 167 cm
x	200 cm
x	183 cm
Weight	495 g
Made in	RO
Guarantee	3 years
Inner Pack Count	1
Quantity Per Box	10
EAN	3342540846081

Related product(s)	EASHOOK OPEN Bm'D Am'D OK MICRO SWIVEL RING OPEN SWIVEL OPEN NEWTON EASYFIT International Version VOLT® International Version
--------------------	---