DJ 300 PRO X DJ 300 PRO X CLUB

Professional 2-in-1 DJ Headphones



DJ 300 PRO X Order # 1001619



DJ 300 PRO X CLUB Order # 1001971

FEATURES

- · Closed-back design
- Maximum flexibility with interchangeable on-ear and over-ear pads
- Accurate cueing due to clear, punchy sound with 45-mm driver
- Long-lasting durability thanks to replaceable components (headband pad, ear pads, cable)
- Locking cable can be connected to the left or right ear cup
- Space-saving transport thanks to a foldable design
- Individual look with customisable caps for the ear cups



DJ 300 PRO X DJ 300 PRO X CLUB

Professional 2-in-1 DJ Headphones

APPLICATIONS

The DJ 300 PRO X and DJ 300 PRO X CLUB are closed-back headphones, ideal for accurate cueing and monitoring. Both provide a clear, powerful sound with focused mids, defined highs and rich bass.

Both models are designed for loud environments such as clubs and festivals and are equally suitable for stylish DJ sets at pop-up events, rooftops, art events or in bare.

Due to interchangeable ear pads, they can be used flexibly as on-ear or over-ear headphones. Sweat-resistant leatherette pads offer comfort, isolation and durability.

The cover caps can be personalised directly via the "MANUFAKTUR" online configurator on the beyerdynamic website.

The cable can be connected to the left or right ear cup and sits securely due to a lockable bayonet lock. The gold-plated mini jack plug (3.5 mm) with a screw-on 1/4" adapter (6.35 mm) is compatible with all standard headphone outputs.

Compact when folded and quick to store — ideal for spontaneous party nights and flexible use.

Replaceable parts ensure sustainable and long-lasting use.

SUPPLIED ACCESSORIES

- 1 pair of on-ear and 1 pair of over-ear pads
- 1.5 m (4.9 ft) special cable (coiled and straight)
- 1 x 6.35 mm (1/4") jack adapter
- Drawstring bag
- Quick start guide

TECHNICAL SPECIFICATIONS

Transducer	Dynamic, 45 mm
Acoustic design	Closed-back
Wearing type	On-ear & over-ear
Frequency response	5 - 35,000 Hz
Nominal impedance	48 Ω
Nominal SPL	
@ 1 mW / 500 Hz	
On-ear	115 dB
Over-ear:	109 dB
Nominal SPL	
@ 1 V / 500 Hz On-ear	122 dB
Over-ear:	122 dB 117 dB
Maximum SPL	117 00
On-ear	122 dB SPL
Over-ear:	117 dB SPL
T.H.D. @ 500 Hz	
On-ear	0.05 %
Over-ear:	0.07 %
Max. short-term power	
handling capacity	10 mW
Ambient noise	
attenuation	20 dBA
Headband pressure	
On-ear	6 N
Over-ear:	7 N
Weight (without cable)	
On-ear	288 g
Over-ear:	315 g
Length and type of cable	1.5 m (4.9 ft) / special cable
	(coiled and straight)
Connection	Gold-plated mini (3.5 mm)
	stereo jack plug &
	1/4" (6.35 mm) adapter

(all specifications acc. to EN 60 268-7)

