











Discharge - Double Ended Hot Restrike

CSR18000/DE

48459

Product information

Double ended compact source rare earth metal halide hot restrike lamps from GE can be used in a variety of applications requiring high luminance, reliability and excellent colour characteristics. Industry Standard outline with hot restrike capability- Dimmable with stable colour- High efficiency with excellent lumen maintenance.

Application areas



Event and Tour



Film and Broadcast







Discharge - Double Ended Hot Restrike

48459

Product data

Cap/Base	30x70mm cylinder, 165mm lead
Bulb Shape	GLS
Bulb Finish	Clear
Bulb Diameter [mm]	73
Maximum Overall Length [mm]	500
Arc Gap	45
Net weight per piece [g]	1280
Gross weight per piece [g]	1370
Operating position	H15 - Horiz 15 degrees
Brand	General Electric (GE)

Performance data

Colour Code	960
Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	6000
Nominal lumens [lm]	1650000
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.323
Nominal chromaticity coordinate Y	0.325
Weighted energy consumption [kWh/1000h]	19800

Electrical data

Nominal power [W]	18000
Nominal lamp voltage [V]	225
Lamp Current [A]	80
Dimming Capability	No
Ballast Required	Yes



Discharge - Double Ended Hot Restrike CSR18000/DE

48459

Logistic data

DUN Code	00043168484596
EAN Code	0043168484596
Pack Quantity	4
Inner pack type	вох
Outer pack type	OUTER BOX
Layer quantity	20 EUR, 24 UK
Layer quantity EUR	20
Layer quantity UK	24
Pallet quantity EUR (PC)	60
Pallet quantity UK (PC)	72
Outer case size	605 x 266 x 276 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination