

PRO-GLOW TAPE®

APPLICATION

Pro-Glow has a non-radioactive chemical light source incorporated into a flexible vinyl film that glows in total darkness after exposure to artificial or natural light. The photoluminescent film light source is designed to absorb energy from any nearby ambient light such as fluorescent lamps or sunlight. Once the source of extraneous light is removed, Pro-Glow film immediately emits a light of its own. There is no limit to the number of times this product can be recharged. When fully charged, Pro Glow provides positive luminance for up to 10 hours. This product is recommended for interior applications only.

FEATURES AND BENEFIT

- Used to spike stages for placement of scenery
- Used for marking exits in dark areas
- Flexible vinyl backing is confirmable and easy to cut to size
- Used to mark light switches
- Can be printed
- Can be die cut to custom sizes and shapes
- Hand-tearable
- Can be classed as no slip in certain circumstances.

TECHNICAL DATA

- Backing : Vinyl Film
- Adhesive : Acrylic
- Thickness : 9 to 11 mils
- Colour: Light yellow/green glossy appearance
- Application Temperature: 50°F to 100°F
- Service Temperature: 20°F to 200°F
- Storage Temperature: Under 70°F and 50% relative humidity
- Typical Adhesive Values:
 - Peel Adhesive Values <u>30 min</u> <u>72 Hours</u>
 - 180° Peel Values 2.5#/in. 4.0#/in.

Note: The above are typical values and should not be used in writing specification.

The information supplied is accurate to the best of Le Mark's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising.



No. 1 Houghton Hill Industries Sawtry Way Houghton, Huntingdon, Cambridgeshire PE28 2DH England Tel: +44 (0)1480 494540 Fax: +44 (0)1480 494206 Email: Info@lemark.co.uk Web: www.lemark.co.uk