

## Floodlight Noctis 24W 1800lm RGBW+CCT+DIMM Wi-Fi/BT Spectrum SMART




CE

---


Power	<b>24 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2260 lm (120°)</b>	Colour of light	<b>CCT/RGB</b>
Beam angle	<b>120 °</b>	IK	<b>07</b>
Degree of protection (IP)	<b>IP65</b>		

---



 User manual



 Declaration of Conformity

**Technical data:**

Code	SLI029045
Power	24 W
Nominal current	115 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Luminous flux*	2260 lm (120°)
Luminous flux**	1800 lm (360°)
Lamp efficacy	75 lm/W
Colour of light	CCT/RGB
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	155 x 146 x 40 mm
Weight	0.49 kg
For use	Inside/Outside
Assembly	On the ceiling
Application	INT/EXT
Other	Variable temperature. Color 2700K / 4000K / 6000K



\*applies to the LED source used. \*\*Luminaire luminous flux