



GLS

22W Non-Dimmable High efficiency LED GLS Lamp

Kosnic's Home range of LED products brings the energy saving capabilities of LED technology to the home. The range is both beautiful and functional while offering lamps that deliver huge energy savings over filament lamps without compromising on brightness. The lamps can quickly replace filament products in general lighting applications, and once in place rapid payback is achieved.

KTC22GLS/E27-N30 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	174
Rated Power (W)	22
CCT Words	Warm White
CCT (K)	3000
Ambient Temperature Range (°C)	-20 to 40
Dimensions L x W x D (mm)	146* \varnothing 80mm
Weight (kg)	0.118
Total Luminous Flux (lm)	2450
Nominal Lifetime (h)	15000
Power Factor	0.55
Blue Light Hazard	RG1
Glow wire temperature(°C)	650

Light Source Specification

Lighting Technology Used	LED
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	E27
Mains / Non-Mains (MLS/NMLS)	MLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	22
Energy Efficiency Class	E
Useful Luminous Flux (lm)	2450
Beam Angle correspondence (in 360°/120°/90°)	in 360°
CCT	3000

On-Mode Power (Pon) (W)	22
Standby Power (Psb) (W)	0
Networked Standby Power (Pnet) (W)	N/A
CRI	82
CRI (min)	80
CRI (max)	84
Height (mm)	146
Width (mm)	80
Depth (mm)	80
Claim of Equivalent Power? (Y/N)	Y
Equivalent Power (W)	150
Chromaticity Co-Ordinates (X)	0.435
Chromaticity Co-Ordinates (Y)	0.403
Peak Luminous Intensity (DLS) (cd)	N/A
Beam Angle (DLS)	N/A
Beam Angle (min)(DLS)	N/A
Beam Angle (max) (DLS)	N/A
Survival Factor (x.xx)	0.9
Lumen Maintenance Factor (x.xx)	0.96
Displacement Factor	0.8
Colour Consistency in Mcadam Ellipses (Mains LED/OLED)	6
LED light source replaces flourescent withouth integrated ballast of particular wattage (Mains LED/OLED) (Y/N)	N
Replacement W Claim (Mains LED/OLED) (W)	N/A
Flicker metric (pst LM) (x,x)	0.1
Storboscopic effect metric (SVM) (x,x)	0.02

Technical Drawings

